

CANYON TONE *Stain*

Technical Bulletin #6 Quick Reference Guide

Following are general guidelines for specifying **CANYON TONE STAIN**. Refer to **CANYON TONE STAIN** Technical Data for more detailed information.

Acceptable Surfaces:

- Concrete (pre-cast or cast-in-place)
- Brick and Block
- Stucco and EIFS
- Masonry Siding (Hardiplank®)
- Man Made Stone Products

Use For:

- Uncoated or Unpainted Surfaces
- Water-Repellent Applications
- Water-Based Product Requirements

Avoid:

- Floors, Decks or Horizontal Surfaces
- Previously Painted Surfaces
- Waterproof Requirements
- Cold Conditions below 40°F (4°C)

PREPARATION:

All surfaces must be clean, dry and cured. Standard power washing is recommended. Do not apply **CANYON TONE STAIN** to any surface that would not be acceptable

for application of premium acrylic house paint.

APPLICATION:

CANYON TONE STAIN is designed to be applied with standard airless spray equipment. It can also be brushed or rolled, although care should be taken to avoid lap or roller marks.

TINTING:

CANYON TONE STAIN can be tinted, using the appropriate tinting base, to virtually any color. While dark colors are generally quite stable, use the same precautions as with premium acrylic house paint when tinting deep reds and yellows.

QUESTIONS:

Refer to the **CANYON TONE STAIN** Technical Data and Application Instructions for complete information on surface preparation, equipment requirements and application instructions. For additional information, please contact our Technical Service Department at 1-800-541-4383.